

Fiber Classifier



INTRODUCTION

The Fiber Classifier segregates a fiber sample into groups of different lengths to allow the proportion of each group to be measured, by weight. Uniform operation is assured by a constant flow of water through the stainless steel inlet system. Chose from models with one to five units.

APPLICATIONS

Pulp

SPECIFICATIONS

- Water flow: 10 liters per minute

FEATURES

- PVC tanks with high surface smoothness prevent loss of fiber due to tank adhesion
- Each tank is driven by its own waterproof motor to provide consistent agitation speed
- Choice of screen sizes: standard ASTM 30, 50, 100 and 200
- Automatic pneumatic clamping of each screen
- Individual fiber collection pots assist in the collection of fiber fractions
- Stainless steel water inlet system
- Control cabinet and sturdy mounting frame

INSTRUMENT SIZE (SINGLE TANK UNIT FRAME)

Depth: 356 mm (14 in.)
Height: 760 mm (30 in.)
Width: 530 mm (21 in.)



WEIGHT

19 kg (42 lb)

CONNECTIONS

Electrical: Specify voltage requirements when ordering

Air: (instrument quality) 600 kPa

Water: 10 liters per minute

ORDERING INFORMATION

Tanks	Catalog number
1	71-03-01
2	71-03-02
3	71-03-03
4	71-03-04
5	71-03-05

note: please specify mesh size for each tank

**The TMI Group
of Companies**



www.testingmachines.com

Vertrieb in Deutschland durch:
Luhne Messtechnik
Inhaber: Herr Dipl.-Ing.(FH) Stefan Luhne
Kölnerstrasse 167
D-41199 Mönchengladbach

Telefon: +49 (0)2166 / 68 18 88
Telefon: +49 (0)2166 / 68 18 20
Telefax: +49 (0)2166 / 146 51 70
Email: info@luhne-messtechnik.de
Internet: www.luhne-messtechnik.de

Messmer Instruments Ltd. Unit F1 Imperial Business Estate, West Mill, Gravesend, Kent DA11 0DL UK
Tel: +44 (0)1474 566488, Fax: +44 (0)1474 560310, e-mail: messmer@testingmachines.com

Büchel BV Fokkerstraat 24, 3905 KV Veenendaal, Netherlands
Tel: +31 (0)318 521500, Fax: +31 (0)318 540358, e-mail: buchel@testingmachines.com